

**Application:** The FDA/USDA compliant PVC White compound offers value in a variety of processing applications, including food processing applications that have limited oil. The all-polyester interwoven carcass provides rot and mildew resistance, low stretch and has excellent fastener retention.

**Technical Data**

	<b>Imperial</b>	<b>Metric</b>
<b>Working Tension</b>	120 PIW	21 KN/M
<b>Number Of Plies</b>	1	1
<b>Fabric Type</b>	Spun Poly	Spun Poly
<b>Top Surface</b>	Smooth	Smooth
<b>Bottom Surface</b>	Friction	Friction
<b>Overall Gauge (Approximate)</b>	0.135 in.	3.4 mm
<b>Weight (Approximate)</b>	0.85 lbs/sq.ft.	4.1 kg/sq.m.
<b>Bottom Coefficient Of Friction</b>	0.30 (approx.)	0.30 (approx.)
<b>Minimum Rec. Pulley Diameters</b>	2.0 in.	51 mm
<b>Elongation At Rated Tension</b>	< 2%	< 2%
<b>Working Temperature</b>	20 to 180 F	-7 to 82 C

**Splicing Methods**

<b>FOF</b>	<b>Finger</b>	<b>Bias Stepped</b>	<b>Skived Bias</b>	<b>Clipper *</b>	<b>Alligator *</b>	<b>Staple *</b>
No	Yes	No	Yes	1 or UX1	7	125

\* Fastener manufacturer should be consulted to review belt and application information.

**Compliance (Government Regulations)**

<b>FDA/USDA</b>	<b>OSHA</b>	<b>MSHA</b>	<b>CSA</b>	<b>FRAS</b>	<b>NCB</b>
	<300 Megohms	CFR 18.65	M422-87	1334.12	158:1989
Yes	No	No	No	No	No

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.