

**Application:** Unique siped ridge Ruffgrip top cover profile provides superior gripping power and is recommended for many incline/decline applications that require safe handling and positive movement. The all-polyester, single-ply interwoven carcass provides low-stretch, excellent fastener retention and good tear resistance. Ideal for conveying luggage, boxes, plastic, paper, corrugated cardboard and wood.

### Technical Data

	Imperial	Metric
<b>Working Tension</b>	150 PIW	26 KN/M
<b>Number Of Plies</b>	1	1
<b>Fabric Type</b>	Spun Poly	Spun Poly
<b>Top Surface</b>	Ruffgrip	Ruffgrip
<b>Bottom Surface</b>	Brushed	Brushed
<b>Overall Gauge (Approximate)</b>	0.320 in.	8.1 mm
<b>Weight (Approximate)</b>	1.20 lbs/sq.ft.	5.8 kg/sq.m.
<b>Bottom Coefficient Of Friction</b>	0.25 (approx.)	0.25 (approx.)
<b>Minimum Rec. Pulley Diameters</b>	2.5 in.	64 mm
<b>Elongation At Rated Tension</b>	< 2%	< 2%
<b>Working Temperature</b>	20 to 180 F	-7 to 82 C

### Splicing Methods

FOF	Finger	Bias Stepped	Skived Bias	Clipper *	Alligator *	Staple *
No	Yes	No	Yes	3 or U3	25	187

\* Fastener manufacturer should be consulted to review belt and application information.

### Compliance (Government Regulations)

FDA/USDA	OSHA	MSHA	CSA	FRAS	NCB
	<300 Megohms	CFR 18.65	M422-87	1334.12	158:1989
No	No	No	No	No	No

No warranty, including implied warranty of merchantability, fitness for a particular purpose, or other warranty of quality is either expressed or implied of this product. The information on this specification sheet supercedes all previously printed material.