

## P-36

### SPECIFICATIONS AND TECHNICAL DATA

Chemprene Specification		<ul style="list-style-type: none"> <li>1612(24)(37A-0).040</li> </ul>
Color		<ul style="list-style-type: none"> <li>Black</li> </ul>
Plies		<ul style="list-style-type: none"> <li>2</li> </ul>
Weight	lbs/Sq ft kgs/m <sup>2</sup>	<ul style="list-style-type: none"> <li>.99</li> <li>4.83</li> </ul>
Available Widths	in mm	<ul style="list-style-type: none"> <li>72</li> <li>1829</li> </ul>
Overall Gauge	in mm	<ul style="list-style-type: none"> <li>.265 ± .020</li> <li>6.73 ± .51</li> </ul>
Recommended working tension @ 2% elongation	lbs/in N/mm	<ul style="list-style-type: none"> <li>150</li> <li>26.8</li> </ul>
Minimum pulley diameter	in mm	<ul style="list-style-type: none"> <li>2.0</li> <li>50.8</li> </ul>
Temperature range	F. C.	<ul style="list-style-type: none"> <li>- 40° to 250°</li> <li>- 40° to 121°</li> </ul>
Meets FDA		<ul style="list-style-type: none"> <li>No</li> </ul>
Compound		<ul style="list-style-type: none"> <li>SBR</li> </ul>
Cover Surface		<ul style="list-style-type: none"> <li>Roughtop</li> </ul>
Bottom Surface		<ul style="list-style-type: none"> <li>Bare</li> </ul>
Coefficient of friction	Cover	1.0
Steel	Bottom	0.3