

P-62M

Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% Tension	16.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	14.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	10.00 in
Minimum Pulley Diameter- Tail	10.00 in

Construction:

Compound Top Cover	Black MOR
Color	Black
Top Cover Thickness (in)	(4.83 mm) 3/16 in
Top Cover Description	Smooth
Compound Bottom Cover	Black MOR
Bottom Cover Thickness (in)	(1.60 mm) 1/16 in
Bottom Cover Description	Smooth
Number of Plies	2
Overall Gauge (in)	(8.73 mm) 11/32 in
Unit Weight- lb/PIW	0.1810 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black MOR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

Splice Instructions:

Splice Step Size	8.00 in
Splice Process	Step Hot

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	#140/R5
Flexco Hinged	#375 or 550
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Belt Strength:

Tension Rating (PIW)	220 PIW
----------------------	---------

Special Characteristics:

Medium oil resistant belt used to resist light traces of oils and terpenes. Widely used in the lumber, recycling and waste water industries. Can be used for some whole grains.

*****All Values are nominal and subject to change without notice.*****