

P-67

Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% Tension	14.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	12.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	10.00 in
Minimum Pulley Diameter- Tail	10.00 in

Construction:

Compound Top Cover	Black MOR
Color	Black
Top Cover Thickness (in)	(3.30 mm) 1/8 in
Top Cover Description	Smooth
Compound Bottom Cover	Polyester
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	2
Overall Gauge (in)	(6.10 mm) 15/64 in
Unit Weight- lb/PIW	0.1420 lbs/PIW
Carcass Type	Polyester Nylon
Compound	Black MOR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

Splice Instructions:

Splice Step Size	8.00 in
Splice Process	Step Hot

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

Belt Strength:

Tension Rating (PIW)	220 PIW
----------------------	---------

Suggested Fasteners:

Flexco Plate/Rivet	#140/R5
Flexco Hinged	N/A
Alligator Staple	#187
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:

This belt is designed for light to medium-duty uses. Ideal for slider bed applications. It features a MOR compound for applications where some oil or wood terpenes are present.

*****All Values are nominal and subject to change without notice.*****