

P-69

Pulley Diameter, Minimum

| | |
|--|----------|
| Min. Pulley Dia. - Head @ 80 - 100% Tension | 16.00 in |
| Min. Pulley Dia. - Head @ 60 - 79% Tension | 14.00 in |
| Min. Pulley Dia. - Head @ 59% Tension or Below | 10.00 in |
| Minimum Pulley Diameter- Tail | 10.00 in |

Construction:

| | |
|------------------------------|-------------------|
| Compound Top Cover | Black Nit |
| Color | Black |
| Top Cover Thickness (in) | (4.83 mm) 3/16 in |
| Top Cover Description | Smooth |
| Compound Bottom Cover | Black Nit |
| Bottom Cover Thickness (in) | (1.60 mm) 1/16 in |
| Bottom Cover Description | Smooth |
| Number of Plies | 2 |
| Overall Gauge (in) | (9.65 mm) 3/8 in |
| Unit Weight- lb/PIW | 0.1810 lbs/PIW |
| Carcass Type | Poly/Nylon |
| Compound | Black Nit |
| Temperature Range (°F)- High | 300 °F |
| Temperature Range (°F)- Low | -10 °F |

Splice Instructions:

| | |
|------------------|----------|
| Splice Step Size | 8.00 in |
| Splice Process | Step Hot |

Other:

| | |
|-------------------|-----|
| Static Conducting | No |
| Cross Rigid | No |
| High Heat | Yes |
| Impression Top | No |
| Oil Resistant | Yes |
| Fire Resistant | No |
| FDA Approved | No |

Belt Strength:

| | |
|----------------------|---------|
| Tension Rating (PIW) | 220 PIW |
|----------------------|---------|

Suggested Fasteners:

| | |
|--------------------|-------------|
| Flexco Plate/Rivet | #190/R5 |
| Flexco Hinged | #375 or 550 |
| Alligator Staple | N/A |
| Clipper Lace | N/A |
| Alligator Lace | N/A |

Special Characteristics:

When oil and heat are present, this compound offers excellent resistance to swelling and cracking. Do not use for dry heat. Oil must be present.

*****All Values are nominal and subject to change without notice.*****