

P-70

Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% Tension	6.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	6.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	6.00 in
Minimum Pulley Diameter- Tail	6.00 in

Construction:

Compound Top Cover	Black SBR
Color	Black
Top Cover Thickness (in)	(0.80 mm) 1/32 in
Top Cover Description	Smooth
Compound Bottom Cover	Poly/Nylon
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	2
Overall Gauge (in)	(3.18 mm) 1/8 in
Unit Weight- lb/PIW	0.0690 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black SBR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

Splice Instructions:

Splice Step Size	8.00 in
Splice Process	Step Hot

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Belt Strength:

Tension Rating (PIW)	150 PIW
----------------------	---------

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#2
Alligator Lace	#15

Special Characteristics:

This belt is compounded to provide excellent abrasion resistance and flex life and is the best buy for the majority of conveyor belt applications. Its high-tension synthetic fabrics result in minimum stretch, great fastener holding ability, impact resistance and the highest adhesion between plies and cover.

*****All Values are nominal and subject to change without notice.*****