

## P-84

COVER GRADE	:	MOR
CARCASS FABRIC	:	EP
NUMBER OF PLYS	:	2 PLY
COVER GAUGE	:	1/8 x BARE 6" VCLEAT
BELT WORKING TENSION (CANNOT EXCEED)	:	220 Lbs/Inch
CONSTRUCTION. WARP	:	Polyester
FILL (WEFT)	:	Nylon
WEAVE TYPE	:	Plain
BELT CARCASS GAUGE	:	0.102"
COVER TENSILE STRENGTH	:	Min. 2100 psi
COVER ELONGATION	:	Min. 400 %
COVER HARDNESS	:	65 ± 5 (SHORE - A)
COVER SPECIFIC GRAVITY	:	1.2 +/-0.05
DIN ABRASION	:	Max. 250 cubic
ADHESION. TOP/PLY	:	40 lbs
PLY/PLY	:	40-50 lbs
BOTTOM/PLY	:	35-40 lbs
BELT O.A.G.	:	0.22" +/- 0.012"
BELT WEIGHT	:	Approx. 10 lbs/ft
% ELONGATION AT WORKING	:	Max. 4%
MIN. HEAD PULLEY DIAMETER IN 60%~80% TENSION	:	10"
TEMPERATURE RANGE	:	-30°C~ +60°C

Note: All results are based on laboratory tests and our present state of knowledge. These are provided as general notes on this product and its uses. This should not therefore be construed as guaranteeing specific properties of the product described or its suitability for a particular application. Please do your own testing and due diligence before using this belt for your application. We reserve the right to alter the technical specification of this product without prior notice.